


Micro Series

Everylite Datasheet Ver 1.2.0

If you liked our Petite, you will love our Micro. It's design allows it to be smaller than Petite, but increasing its waterproof rate to IP68. With its new technology it has a 170° optical lens providing better light distribution and allowing fewer modules meaning more savings by having 3.5 modules per foot. The cable is thicker and longer, which permits it to work better with accessories such as wire nut and connectors. Finally, we added an extra mounting hole to offer a solution for installation purposes, given the fact that the module is too small to be placed with silicone.



Micro Parameters

Item #	Color	Peak Wave Length	module/ft	Lm/module	Lm/ft	Lm/W	W/module	W/ft	Viewing Angle	Waterproof
MC-2D-W3CL	White	3000K	3.5	22.5	78.8	62.5	0.36	1.26	170°	IP68
MC-2D-W6CL	White	6500K	3.5	25	87.5	70	0.36	1.26	170°	IP68
MC-2D-RXCL	Red	620-625nm	3.5	11	38.5	31	0.36	1.26	170°	IP68

Power Supply Maximum Loading Capacity (50 modules per run)

Power Supply	20W	30W	60W	100W	150W
By Module	50 m	75 m	150 m	250 m	375 m
By Footage	14 ft	21.5 ft	43 ft	71.5 ft	107 ft

Drawing

